

LOCTITE® LB 771™

Known as LOCTITE® Nickel Anti-Seize Lubricant
January 2015

PRODUCT DESCRIPTION

LOCTITE® LB 771™ provides the following product characteristics:

Technology	Nickel Based
Chemical Type	Mineral oil, nickel, graphite
Appearance	Thick metallic, silver paste, without separation
Viscosity	Flow similar to mustard
Cure	Non-curing
Application	Anti-seize
Specific Benefits	Provides long life slow speed parts Nickel content stays intact up to 1315 Prevents galling of parts especially stainless steel

LOCTITE® LB 771™ is a heavy-duty, high temperature, anti-seize lubricant that resists galling and corrosion and reduces wear in heavy pressure applications. It contains tenacious metals, oils and graphite materials which cannot be burned away or removed by slow moving parts. It is exceptionally resistant to attack by acids, ammonia, acetylene and vinyl monomer. LOCTITE® LB 771™ reduces friction for tight assembling of stainless steel threads and press fits. Allows easy disassembly of parts after exposure to corrosive or hot environments. Typical applications include lubricating drop forge dies and hammers, catalyst bed and reaction chamber supports, conveyor chains, and chemical plant bolts for pump housings and pipe flanges. It also lubricates and seals pipe threads in acid environments and coats gaskets in high temperature applications. This product is typically used in applications with an operating range of -54 °C to 1,315 °C

TYPICAL PROPERTIES OF UNCURED MATERIAL

Specific Gravity @ 25C 1.1

Slat Fog Corrosion, ASTM B 117 hours 168

Extreme pressure Test, ASTM D 2509 m/min 123

Flashpoint - see SDS

Viscosity, Brookfield - RVT, 25C mPa*s(cP):

Spindle TE, speed 2.5 rpm 650,000 to 1050000^{LMS}

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen-rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Directions for use

1. Stir LOCTITE® LB 771™ well before using
2. For best results, remove dirt, oil and grease
3. Apply a light coating of LOCTITE® LB 771™ to parts requiring protection
4. Assemble parts
5. Wipe away excess lubricant, protection of parts is now assured
6. To prevent contamination of unused products, do not return any material to its original container
7. **CAUTION:** LOCTITE® LB 771™ is not a high-speed load-carrying lubricant and should not be used on ball or roller bearings, or on parts where lubrication is critical
8. **NOTE:** It is not recommended for high-stress grade 8 bolts where stress corrosion may occur

Loctite Material Specification^{LMS}

LMS dated July-28, 1998. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

Reference - Preliminary

Storage

Store the product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal storage: 8C to 21C. Storage below 8C or greater than 28C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return the product to the original container. Henkel Corporation cannot assume responsibility for a product that has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.



Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.5

