

DID YOU KNOW?

about our... **SPAGHETTI ROLL CONTINUOUS PLUGS**



CONXTRUCT

**NEW
PRODUCT**

The Spaghetti roll plugs are suitable for light duty anchoring in concrete, solid brick, solid block and stone. Simply pre-drill the base material, push the spaghetti in and cut-off at the required length. Complete the installation with a screw or nail through the fixture and into the spaghetti-plug.

Applications

- » Electrical conduit saddles, light fixtures and brackets
- » Installation of signage into solid materials
- » Plumbing pipe clamps and saddles
- » Miscellaneous – mounting of letterboxes, hose reels, CCTV cameras, alarm sensors & sirens, cupboards into solid materials, towel rails, etc.



For use with minimum 3.5mm nails or 6 or 8 gauge screws



The roll enables you to cut the plugs at the desired length to suit the fixing application.




SPAGHETTI ROLL CONTINUOUS PLUG 5.0 PLASTIC / HEC GREEN

Part	QFind	Drill Dia Ø (mm)	Length (m)	Screw Gauge	Nail Size (mm)	Plastic Thickness µm	Colour	Pack Qty
MWPSR50050	SR5050	5.0	50	6	3.5	100	Green	1


SPAGHETTI ROLL CONTINUOUS PLUG 5.5 PLASTIC / HEC RED

Part	QFind	Drill Dia Ø (mm)	Length (m)	Screw Gauge	Nail Size (mm)	Plastic Thickness µm	Colour	Pack Qty
MWPSR55050	SR5550	5.5	50	6 or 8	3.5 - 4.0	100	Red	1
MWPSR55005	SR5505	5.5	5	6 or 8	3.5 - 4.0	100	Red	1


Installation




1. Drill 5.0-5.5mm diameter hole. Drill hole to required depth so that screw or nail can be driven home.



2. Clean hole thoroughly of dust and debris.



3. Insert spaghetti wire to full depth of hole and cut off.



4. With fixture firmly held in place fasten with a 6 or 8 gauge screw or minimum 3.5mm nail.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**

